



GIOTTO



- Linea arrotondata priva di spigoli e facile da pulire.
- Perno di scorrimento, cromato rettificato e lappato.
- Boccole di scorrimento autolubrificante.
- Paracolpo su carrello in gomma vulcanizzata.
- Coperchio supporto vela smontabile.
- Parafetta rimovibile in acciaio inox con incastro rapido a baionetta.
- Tutte le minuterie acciaio inox.
- Copertura inferiore con coperchio per accesso diretto ai componenti elettrici.
- Scheda elettromeccanica commutabile 110-220V monofase e 380V trifase.
- Affilatoio con vaschetta inferiore di protezione.
- Sistema di tenuta stagna su puleggia.
- 41 mm di distanza fra la lama e il corpo macchina.

GIOTTO

- Manopole in plastica.
- Piedini in gomma.
- Interruttore isolato IP 44

GIOTTO TOP

- Manopole in alluminio.
- Piedini in alluminio telescopici con base in gomma.
- Pulsanti IP 67 in acciaio inox

GIOTTO BS

- Braccio stringi salumi con staffa in acciaio inox.

GIOTTO VCO

- Particolarmente richieste nei mercati nordici.
- Piatto a vasca per tagliare ogni tipo di prodotto.
- Staffa blocca prodotto in alluminio smontabile con chiodi in acciaio e denti fresati sul lato lama.



GIOTTO 300 BS TOP

- Innovative rounded design and no sharp edges or visible screws.
- Chrome plated ground and lapped slide rod.
- Self lubricating slide rod bushings.
- Vulcanised rubber stops on carriage.
- Removable support cover for thickness gauge plate.
- Stainless steel slice deflector with snap-on bayonet fitting.
- Stainless steel screws and fittings.
- Bottom cover for accessing electrical components.
- Changeover electronic circuit 110-220V single and 380V three-phase
- Built-in sharpening tool with bottom protection
- Enclosed and sealed belt pulley
- 41 mm distance between blade and motor

GIOTTO

- Plastic knobs.
- Rubber feet.
- Switch with IP44 protection rating.

GIOTTO TOP

- Aluminium knobs.
- Aluminium telescopic feet with rubber base.
- S/Steel pushbuttons with IP67 protection rating.

GIOTTO BS

- Easy to remove stainless steel meat grip arm.

GIOTTO VCO

- Specially required by the Northern European marketplace.
- Product table designed to slice all types of products.
- Removable aluminum end weight.
- Designed with grooves: nails underneath.



GIOTTO 300 VCO TOP



GIOTTO 300 BS






1. Zavorra smontabile BS
Removable food pusher BS



2. Ampio spazio tra lama e corpo macchina
More space between blade and body machine



3. Spazioso piano per appoggio prodotto
Large hopper



	Ø Lama Ø Blade Ø Messer Ø Lame	Motor Motor Moteur	Spessore taglio Cut thickness Schnittbreite Épaisseur de coupe	Corso carrello Run of carriage Wagenschub Course du chariot	Piatto Hopper Wagen Plateau	A	B	C	D	E	F	G	L	X	Y	H	W	Peso netto Net weight Nettogewicht Poids net	Dimensioni imballo Shipping Verpack, abmessungen Dim. emballage	Peso lordo Gross weight Bruttogewicht Poids brut
	mm/inch.	watt/Hp	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg	mm	kg
GIOTTO 250 BS / Top	250/10"	210/0,29	30	275	275x260	425	320	550	540	435	790	550	620	255	190	190	190	27	800x600x520	30
GIOTTO 275 BS / Top	275/11"	210/0,29	30	275	275x260	425	320	560	540	450	790	560	620	255	205	205	205	28	800x600x520	31
GIOTTO 300 BS / Top	300/12"	210/0,29	30	275	275x260	425	320	580	540	460	790	570	620	255	220	220	220	29	800x600x520	32
GIOTTO 250 VCO / Top	250/10"	210/0,29	30	275	250x240	425	320	550	590	435	640	475	540	240	190	190	190	26	800x600x520	29
GIOTTO 275 VCO / Top	275/11"	210/0,29	30	275	250x240	425	320	560	590	450	640	485	540	240	205	205	205	27	800x600x520	30
GIOTTO 300 VCO / Top	300/12"	210/0,29	30	275	250x240	425	320	580	590	460	640	495	540	240	220	220	220	28	800x600x520	31

Ø Cuchilla
Ø Lámina
Ø лезвия
刀片直径

Motor
Двигатель
电机

Esponsor corte
Espessura corte
Толщина нарезки
切削厚度

Desplazamiento del carro
Escorrimiento carrinho
Ход каретки
料斗行程

Piatto
Лоток
料斗

A B C D E F G L X Y H W

Peso netto
Peso líquido
Вес нетто
净重

Dimensiones embalaje
Dimensões embalagem
Размер упаковки
包装尺寸

Peso bruto
Peso bruto
Вес брутто
毛重

