

ET-O Belt

Picture coming soon

ET-O Belt

The ET-O Belt is a stationary mounted depositor with a dynamic hopper and offline feature that makes it easily maneuverable for cleaning and switching depositing parts. Built-in lifting table included.

Picture coming soon

Stationary mounted depositor with dynamic hopper movement and off-line facility for easy cleaning and change of depositing parts. A variety of piston diameters can be supplied to suit a specific application. The belt line depositors have a built-in lifting table. The ET-O belt line depositor is available for 1000, 1200 and 1500 mm lines, working widths ranging from 870 to 1370 mm, however, the depositor can be made to suit any existing lines as well. Operation is very simple via the intuitive touch screen menu. Further, the depositor can be connected to the internet, if any sort of support is needed.

UPS/EFU

- Suitable for masses of high viscosity
- Handles liquids perfectly as well
- Easy cleaning and maintenance
-
- Dynamic hopper movement
- Easy and simple to operate

Picture coming soon

The Aasted Machinery Program

Find the technical specifications for the machine below.

	ET-O Belt 1000	ET-O Belt 1200	ET-O Belt 1500
Capacity (kg/hour)	14000	18000	22000
Length (mm)	3200	3400	3700
Width (mm)	2000	2000	2000
Height (mm)	1930	1930	1930
Power usage (KwH)	22	22	22
Air usage (m3)	-	-	-
Water usage (m3)	0,013	0,014	0,016
Weight (kg)	4300	4500	5200

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- ET (C-Frame)
- ET-O (C-Frame)
- ET-O Chain