
MATURING-AFTERMATURING

OUR CLIMATIC/E-MODELS IN OVERVIEW

Modell		2500	3000	3002	3003
Capacity	max ca. kg	55-200	110-400	220-800	330-1.200
Number trolley		1	1	2	3
Measures					
Trolley rows		1	1	1	1
Trolley neasure	ca. cm	80x80x155	100x100x200	100x100x200	100x100x200
Fixed layers	ca. cm	90			
Smoke stick length	ca. cm	80	100	100	100
Heating	ca. cm				
Width A	ca. cm	135	175	175	175
Width with control B	ca. cm	180	220	220	220
Depth C	ca. cm	145	205	335	433
Height D	ca. cm	225	255	255	255
Cooling power	KCal/h	2.000	2.500	4.000	5.500
Electric supply 400V 50HZ	ca. kW	6	8	10	12





changes reserved









Maturing-Aftermaturing





MATURING-AFTERMATURING

CLIMATIC/E

The Climatic maturing- after maturing units serves to refine different high quality products like every type of raw sausage and meat products, mould products, air dried meat- and sausages as well as cheese.

Work processes like reddening, drying, maturingafter maturing and storing makes this units to all-round applicable machines.

ADVANTAGE OVER ADVANTAGE...

- cooling machine integrated
- chamber in modular construction double walled and complete with bottom
- whole plant with special isolation therefore nearly no energy loss. Walls and door out of galvanized sheet steel with polyester varnish (RAL 9010)
- all edges inside are rounded, therefore highest possible hygiene
- Drive-in ramps (only for loading trolley)
- Door to open also from the inside because of safety reasons
- Temperature/humidity will be controlled about microprocessor
- Control selectively about microprocessor or touch screen as optional
- For fixed installed stainless steel frame inside or standard loading trollies 80x80xh 155 cm or 100x100x200 cm








Drive-in ramps









Hook for Bacon



Smoke stick with starprofile



Computer control (standard)

Possibility of 50 different production programs with each 40 work steps to store, therefore possibility to produce a lot of different products. At this every time it is possible to intervene during the running program. It is possible also to record the data about PC.



Touch screen

With coloured graphic screen, easy handling, possibility of remote monitoring by modem (MICRO CCS).





