Hollymatic Tenderizer

Tender Rite

Powerful, Safe, & Efficient Tenderizing & Slicing

Specifications

CONSTRUCTION:

Hygienically superior design with all stainless steel housing and inlet. Stronger tenderizing blade assemblies are built for long life.

MOTOR:

¾ HP, 115 Volt, 60 Hz, 1 phase On/Off switch with safety shutoff on lid Blade Assembly: Tenderizing Deep Cut

ADDITIONAL OPTIONS:

- Slicing Blades: 10 mm or 20 mm
- Double Tenderizing: (2) Tenderizing assemblies in one operation

DRIVE:

Oil bath gear drive mechanism provides dependable self-lubrication

DIMENSIONS:

Length » 16.95 inches Width » 15.75 inches Height » 15.35 inches

Weight » 80 lbs

SPEED:

1200 steaks per hour



Optional Double Tenderizing







Optional Mini Slicer



FURB PROCESSING EQUIPMENT SINCE 1937

Hollymatic Warranty: Six (6) months from date of purchase.

Refer to warranty certificate for terms and conditions.

© Copyright Hollymatic Corporation. All Rights Reserved.

708/579-3700 v. 708/579-1057 f. hollyinfo@hollymatic.com www.hollymatic.com