



# MITSUBISHI TRACTOR

## MT25

High Quality & the Stylish Tractor





## SPECIFICATION

Model			MT25 GEAR	MT25 HST
Engine	Model		Mitsubishi S3L2	
	Type		4 cycle, Water cooled Diesel	
	Max. output	PS	25.9(18.8kw) / 2500rpm	
	PTO Horsepower	PS	21.8 (15.8kw)	20.2 (14.7kw)
	Number of Cylinders		3	
	Total Displacement		cc	1318
Fuel System	Fuel Capacity		L	
	Injection Type		I.D.I	
Drivetrain	Clutch Type		Dry - Single	
	Transmission		Constant(main)	HST
	Number of Speeds		F8-R8	2 Range
	Shuttle (F-R)		Synchro	N/A
	Brakes Type		Wet-Disc	
Hydraulics	Position Control		Standard	
	Main Pump Capacity	L/min	22.1	
	Steering Pump Cap.	L/min	10.1	
	Auxiliary valve		Option	
	Draft Control		N/A	
PTO	Type		Trans	Live
	Rear PTO Speed	rpm	540 @ 2376	
	Mid PTO Speed	rpm	Option(2000)	
Steering	Steering System		Hydrostatics (Standard)	
	Turning Radius W/Brake	m	2	
Hitch	Type		Category 1	
	Lift Capacity (at ball-end)	kg	1000	
Tire	AG Tires	Front	7-12	
		Rear	9.5-16	
	Turf Tires	Front	23x8.5-12	
		Rear	33x12.5-16.5	
Dimensions	Overall Length	mm	2775	
	Overall Width	mm	1380	
	Over Height	mm	2140	
	Ground Clearance	mm	290	
	Weight Total	kg	825	845

