## 130

to medium packaging capacities. The bag seals food products, industrial or consumer goods and can therefore improve their protection, storage, maturing or the final presentation for the customers.

Thanks to the WEBOMATIC CleanDesign® inspired surface the external fied and quickened due to the modified sealing bar, which can be

The sealing bar's spring loaded end pieces do not only ensure a perfect

For easier maintenance and better access to the inner part of the machimachine. At any time, the I 30 can be upgraded with MAP or soft-air

## **Technical Data** Design Stainless steel **Chamber dimensions** 460 x 580 x 200 mm (W x D x H) 525 x 850 x 850 mm (W x D x H) Machine dimensions Length of sealing bar, longitudinal 1 x 450 mm Weight approx. 141 kg Compressed air **Control unit** IGT-standard Vacuum pump 63 m<sup>3</sup>/h 1.7 kW **Electric power Options** MAP • soft-air Gas supply Post connector with NW 9







## C € EH[





Technical changes reserved. All WEBOMATIC machines comply with the valid European regulations according to CE, EMC, EAC.

Maschinenfabrik GmbH Hansastr. 119 44866 Bochum/Germany

Telephone +49 (0) 2327-3099-0 +49 (0) 2327-3099-29 Telefax info@webomatic.de

www.webomatic.de

