



# MAM TECHNICAL INFORMATION

PRODUCT		TRACTOR GX series		Unit: mm / kg	
Subject		SPECIFICATION		Date: 2009/5/8	
TRACTOR MODEL		GX3600		Remarks	
<u>Engine</u>	Type	Water cooled 4-cycle, 3 - cylinder diesel			
	Engine Model	Mitsubishi S3L3L			
	Engine output(HP)	36		Max	
	Rated RPM(RPM)	2600			
	Number of cylinder	3			
	Displacement (L)	1.662			
	Battery (V / Ah )	12/36			
	Fuel tank capacity (L)	30			
<u>Dimensions</u>	Front tyre(AG)	(7.50-16)		Std. size at Japan	
	Rear tyre(AG)	(12.4-24)		Std. size at Japan	
	Tread	Front(mm)	1115		reference
		Rear(mm)	1090		reference
	Wheelbase(mm)	1650			
	Overall length(mm)	2780		w/o 3P	
	Overall width(mm)	1410			
	Height(mm)	1480		Steering	
	Ground clearance (mm)	380			
	Turning Radius(m)	2.5		w/ brake	
Weights(kgf)	1150				
<u>Power Train</u>	Clutch	Dry, Single			
	Transmission type	Constant(main)			
	Speed steps	F8- R8			
	Shuttle transmission	Synchro			
	Brake type	Wet disk			
	Parking brake	Latch type			
	Rear PTO	STD			
	PTO RPM	590/850		Standard rotating	
	PTO shaft	SAE 1 - 3 / 8, 6 - sprine			
	Live or IND PTO	NA			
Mid PTO	NA				
<u>Hitch</u>	Category	Cat. 1			
	Lift capacity at hitch ball (Kgf)	1200			
	Position Control	STD			
	Draw bar	N.A.			
<u>Hydraulics</u>	Pump capacity (liter/min.)	Main	29.0		
		P/S	13.2		
	Hydraulic outlet block	STD 1			
	Auxiliary valve	N.A.			
	Max. Pressure (kgf/cm <sup>2</sup> )	155			
Oil filter type	Cartridge type				
<u>Notes</u>	ROPS	N.A.			
	Tyre	Thailand supply			

