

Scales

MARELEC W8-D4

Accuracy

Fast weighing

Robust construction

Computer
connectivity

MARELEC W8 platforms are designed to meet the most severe requirements to weigh on shore. Accuracy, flexibility, robust construction and user-friendliness are getting full attention. In addition to this, MARELEC scales are incredibly fast: measurement speed is maximum 0,5 seconds. The scales are available with the MARELEC D4 indicator executed as stand-alone type or on gooseneck.

MARELEC scales are designed to handle most weighing jobs, even in the most humid conditions.

The weighing systems can be equipped with a series of adjustable printers, data processing and report programs. Software can be adapted to your specific needs and specific production requirements.



MARELEC D4 - Indicator

FUNCTIONS*

Precision on nominal weight:
0,05%.

Measurement speed :
maximum 0,5 seconds

Electronic digital indicator with
high-low alarm on target value

EXECUTION

Platform of stainless steel
type AISI 316L

Loadcells hermetically
protected IP67

Security against mechanical
overload integrated

Stainless steel indicator IP67
with integrated electronics

FEATURES

- Construction : Stainless steel AISI 316L. All vulnerable parts are built in hermetically. The system does not contain any moving mechanical parts
- Labeling : Each scale can be equipped with a printer adapted to your needs
- Power supply : 230VAC/5W
- Protection : Protected against mechanical overload
Loadcells hermetically protected IP67
Optional protection frame against rough handling
- Traceability : MARELEC weighing systems can easily be integrated in processing traceability data
- User-friendly : Easy to use, easy to clean

WEIGHING RANGE AND WEIGHING PLATFORM/MODEL

Model	Weighing range	Weighing platform
W8/6-D4	0 - 6 kg	325x325mm
W8/15-D4	0 - 15 kg	325x325mm
W8/30-D4	0 - 30 kg	325x325mm
W40/15-D4	0 - 15 kg	400x400mm
W40/30-D4	0 - 30 kg	400x400mm

Indicator MARELEC D4

- Construction : Stainless steel hermetically protected to IP67 standards - Integrated electronics
- Indicator : 14 segment display with 8 red illuminating characters (14 mm high)
- Selection : 4 push buttons integrated in the control panel
- Mounting : On gooseneck
- possibilities : Option: stand alone with 3 m cable
- Functions : Labeling: 50 user-programmable species
Auto-tare function
Forward and reverse grading in 14 grades
Statistical print report
- Option : Battery operation

MARELEC Food Technologies

Redanweg 15
8620 Nieuwpoort
Belgium
T +32 58 222 111
F +32 58 239 280
sales@marelec.com

* Subject to modifications

