

ET (C-Frame)

Picture coming soon

ET (C-Frame)

The ET (C-Frame) is easily maneuverable for cleaning and re-positioning on the production line.

With its C-frame, the depositor is easy to move around for cleaning or placing in another position on the line. A variety of piston diameters can be supplied to suit a specific application. Lifting table can be incorporated in the depositor, if needed. The ET C-frame depositor is available for Midi, Maxi and Jensen Flex lines, working widths ranging from 350 to 600 mm, however, the depositor can be made to suit any existing lines as well. Operation is very simple via the intuitive touch screen menu. Further, the depositor can be connected to the internet, if any sort of support is needed.

UPS/EFU

- The C-frame design enables frequent production change-overs
- Can handle masses of high viscosity as well as liquids
-
-
- High flexibility
-

Picture coming soon

The Aasted Machinery Program

Find the technical specifications for the machine below.

	ET (C-Frame) Midi	ET (C-Frame) Maxi
Capacity (kg/hour)	1000	1450
Length (mm)	1405	1605
Width (mm)	900	900
Height (mm)	1650	1650
Power usage (KwH)	5	5
Air usage (m3)		2,5
Water usage (m3)	0,007	0,01
Weight (kg)	800	850

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- ET-O (C-Frame)
- ET-O Belt
- ET-O Chain