

Model START AUTO 300/350 SBR

DESCRIPTION

START AUTO SBR is a powerful automatic slicer that can also be used manually. Sturdy and high performing: carriage speed selection from 0 up to 60 slices/min. Easy to use, easy to clean. Ideal for supermarkets, restaurants, catering companies, laboratories.

FEATURES

Two available sizes: with 300 mm or 350 mm blade. Anodized aluminium casting construction: sturdy and light weight.

High quality hardened chromium steel alloy blade. Powerful and noiseless continuous use motor. Multygrip belt drive: always the right grip. Special product holder with adjustable fence and threeposition heavy food pusher.

Large clearance between the back of the blade and the base provides access for easy cleaning (pict.1). Slice thickness precision adjustment: gasket-sealed mechanism (pict. 2).

Drip deflecting edge of the gauge plate: adjustment mechanism is protected (pict. 3). No-drip edge base: easy cleaning (pict. 4). Stainless steel ball-bearing blade pulley and special moisture-proof gasket.

Equipped with **SBR** (Safe Blade Removal) (pict. **5**). Built-in sharpener, removable for cleaning purposes: simple and convenient.

30° carriage angle: good visibility of the slice exit area and better ergonomy.





















Model START AUTO 300/350 SBR



AVAILABLE CONFIGURATIONS

ANODYZED



All external aluminium parts are silver anodyzed: TRADITIONAL SILVER FINISHING.

BASIC QUANTANIUM



Gauge plate, blade and blade cover disc are non-stick coated. Remaining aluminium parts are anodyzed: CHEESE CUTTING IS NO MORE A PROBLEM.

TOTAL QUANTANIUM



All external aluminium parts are black QuanTanium non-stick coated to be resistant to all detergents: THE BLACK APPEAL.

STANDARD OUTFIT



SBR auick release disc



User Manual, CE compliance declaration and "TEN BASIC RULES" Cardboard.



FAST CLEANER detergent, Cleaning nylon brush, Oiler.

AVAILABLE OPTIONALS



Non stick coated blade, perfect for cheese and fish cutting. Already included in

Quan**T**anium[®] configuration.



Stainless steel chute for vegetable cutting.

QuanTanium® with Titanium particles reinforced three-layernon-stick coating will allow:

smoothness: difficult products


like cheese or fresh meat do not stick and products slide smoothly and frictionless;

- higher resistance to abrasion;
- resistance to most aggressive detergents.





DIMENSIONS



SPECIFICATIONS AND SHIPPING INFORMATION

	0	HP	9	8 📆	***	k.B.
Model name	Blade mm	Power Hp/kW	Drive	Cut Capacity mm	Cut thick. mm	Net weight kg
START AUTO 300 SBR	300	0,48/0,37	Belt	285x165 O 190	20	43
START AUTO 350 SBR	350	0,48/0,37	Belt	280x190 O 220	20	45

All voltages and frequencies are available on request.

SHIPPING

Dimension	Weight
cm 83 x 73 x 71	50 kg
cm 83 x 73 x 71	52 kg

