

ET-O Chain



ET-O Chain

The ET-O Chain is a stationary mounted depositor with a dynamic hopper and offline feature that makes it easily maneuverable for cleaning and switching depositing parts. Built-in lifting table with integrated mold shaking included.

Picture coming

Stationary mounted depositor with dynamic hopper movement and off-line facility for easy cleaning and change of depositing parts. A variety of piston diameters can be supplied to suit a specific application. The chain line depositors have a built-in lifting table with integrated mould shaking. The ET-O chain line depositor is available for 1000 and 1200 mm lines, working widths ranging from 870 to 1070 mm, however, the depositor can be made to suit any existing lines as well. Operation is very simple via the intuitive touch screen menu. Further, the depositor can be connected to the internet, if any sort of support is needed.

UPS/EFU

- Quick change-overs
- Dynamic hopper movement
- Easy maintenance and cleaning
-
- Perfectly handles masses of high viscosity as well as liquids
- Easy and simple to operate



The Aasted Machinery Program

Find the technical specifications for the machine below.

	ET-O Chain 1000	ET-O Chain 1200	ET-O Chain 1500
Capacity (kg/hour)	14000	18000	22000
Length (mm)	3200	3400	3700
Width (mm)	2000	2000	2000
Height (mm)	1930	1930	1930
Power usage (KwH)	22	22	22
Water usage (m3)	0,013	0,014	0,016
Weight (kg)	4300	4500	5200

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- ET (C-Frame)
- ET-O (C-Frame)
- ET-O Belt