

filler pot

POT FILLER

This machine is designed for the potting of spreadable creams of medium and high density and viscosity. The gear pump is built of alimentary grade aluminium and can inject at pressures of up to 4 atmospheres. The body of the pump can be completely dismantled and cleaned in just a few minutes and thus facilitates the changing of the cream to be potted. It is particularly suitable for clients who produce pastes and alimentary conserves of all types.

TECHNICAL DATA

Electrical specification: 220 V single phase 50 Hz
Power required: 0,9 Kw - 16 A - 3 poles
Tank capacity: 6 Kg
Hourly production rate: 50 Kg
Dimensions: h. 700 mm, w. 380 mm, d. 380 mm



galileo

ROTATING MACHINE FOR HOLLOW

Completely constructed in stainless steel • Safety clutch mechanism on orbital rotation • Speed controlled via inverter

This machine, which is entirely built in AISI 304 steel, allows the mould to be fixed into double permanent magnets. It is equipped with a safety clutch mechanism and allows the simultaneous use of 4 workstations.

The speed can be adjusted via an inverter and the transmission is supplied with a mechanical safety clutch.

TECHNICAL DATA

Electrical specification: 220 V single phase 50 Hz
Power required: 0,4 Kw - 16 A - 3 poles
Dimensions: h. 1430 mm, w. (total) 570 mm, d. 1000 mm
Foot pedal controlled
Max weight per arm: mould containing 3 Kg of chocolate

