

Alice™ C-Frame Single



Alice™ C-Frame Single

Choose the Alice™ C-Frame depositor in single head configuration and you can deposit, extrude or wire-cut single masses.

Choose the Alice™ C-Frame depositor in single head configuration and you can deposit, extrude or wire-cut one mass. The C-Frame design and integrated electrical cabinet gives you full flexibility. The machine is easily fitted to existing lines and seamlessly turned on or offline. The integrated conveyor has X (side-to-side) movements. All programming is done from a color touch screen and can be adjusted in real time. The machine is easy to clean. The Alice™ hopper also makes the depositor adaptable to quick product changes thanks to its off-line capability. Upgrades to double or triple head configuration are possible.

UPS/EFU

- High mobility
- Modular design
-
-
-
-



The Aasted Machinery Program

Find the technical specifications for the machine below.

	Alice™ C-Frame Single 600	Alice™ C-Frame Single 400
Length (mm)	1867	1667
Width (mm)	1509	1509
Height (mm)	1829	1829
Power usage (KwH)	16	16
Air usage (m3)	75L/min. 6 bar / 4.5	75L/min. 6 bar / 4.5

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- Alice™ C-Frame Double
- Alice™ C-Frame Triple