SE14-O-DHD







SE14-O-DHD



The SE14-O-DHD is a stationary mounted depositor with dynamic hopper movement. Equipped with a detachable hopper for easy cleaning and change of depositing parts.

Stationary mounted depositor, mainly for Aasted lines, with dynamic hopper movement. With its detachable hopper and depositing parts, it is easy to change hoppers and depositing parts for running of another product or cleaning.

The SE14 represents the ultimate depositor with its supreme build quality. All axes are servo driven and extremely strong for handling even the most difficult masses. A wide variety of piston diameters can be supplied to suit the smallest pralines or chips up to tablets with big inclusions. The hopper can be divided into multiple compartments for multi-color or one-shot depositing. The SE14 depositors have built-in lifting table with integrated mould shaking. The SE14 depositor is available for 700 and up to 1200 mm lines, working widths ranging from 580 to 1080 mm. Operation is very simple via the intuitive touch screen menu. Further the depositor can be connected to the internet, if any sort of support is needed.

UPS/EFU

- Easy to operate
- Easy cleaning and maintenance
- •
- •
- High quality machine
- Low energy consumption





The Aasted Machinery Program

Find the technical specifications for the machine below.

Capacity (kg/hour) Length (mm) Width (mm) Height (mm) Power usage (KwH) Air usage (m3) Water usage (m3)	SE14-O- DHD 1000
Width (mm) Height (mm) Power usage (KwH) Air usage (m3)	16320
Height (mm) Power usage (KwH) Air usage (m3)	1850
Power usage (KwH) Air usage (m3)	2100
Air usage (m3)	850
	29
Water usage (m3)	-
riator adago (mo)	0,013
Weight (kg)	2830

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

• test	• SE14-C-DHD	• SE14-O
• SE 13-O Belt	• SE14-C-O	• SE14-O-OFL
• SE14-Basic	• SE14-C-O-DHD	• SE14-O-OFL-DHD
• SE14-C-Basic	• SE14-DHD	• SE14-S-Basic