

EP2 (C-Frame)



EP2 (C-Frame)



The EP2 (C-Frame) is easily maneuverable for cleaning and re-positioning.

A wide variety of piston diameters can be supplied for production of the smallest pralines up to tablets with big inclusions. The hopper can be divided into multiple compartments for multi-color or one-shot depositing. A lifting table can be incorporated in the depositor, if needed. Multiple choices of agitator types are available. The EP2 C-frame depositor is available for Midi, Maxi and Jensen Flex lines, working widths ranging from 350 to 600 mm. However the depositor can be made to suit any existing line as well. Operation is very simple via the interactive touch screen menu. Further, the depositor can be connected to the internet, if any sort of support is needed.

UPS/EFU

- Flexible
- Fully computerized control
- Value for money
- Satisfying frequent production
- One-shot technology
- Handles solid masses



The Aasted Machinery Program

Find the technical specifications for the machine below.

	EP2 Midi	EP2 Maxi
Capacity (kg/hour)	2100	3000
Length (mm)	1405	1405
Width (mm)	900	900
Height (mm)	1650	1650
Power usage (KwH)	7	7
Air usage (m3)	5	5
Water usage (m3)	0,007	0.01
Weight (kg)	800	800

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- EP2-O (C-Frame)
- EP2-O Belt
- EP2-O Chain