

# Master Bottomer Chocolate/Compound/ Sugar Coating

Picture coming soon

# Master Bottomer Chocolate/Compound /Sugar Coating



The Nielsen Master Bottomer is supplied in belt widths from 850 mm up to 2600 mm and is suitable for all bottom enrobing such as doughnuts, biscuits, etc.

The Master Bottomer is designed for medium volume and long run and short run production of a wide range of products with different quality demands.

The Master Bottomer provides bottom enrobing of for example soft creams and caramels.

State of the art design and features ensure consistent high quality reliability and performance. All components including the frame and panels are in corrosion resistant stainless steel. Furthermore the high-quality design means operational reliability in three-shift production, seven days a week.

The Master Bottomer can either be supplied in the working direction left to right, or right to left.

This bottomer enrober is equipped with Allen-Bradley or Siemens PLC and Touch Screen and can be supplied in working direction left to right, or right to left.

## UPS/EFU

- Stainless steel and groundbreaking design
- Detachable lower section
- Documented reliability in three-shift operation
- Slow-running, temperature-neutral chocolate pumps
- Uniform coating of products
- Precision engineering

  
Picture coming soon

# The Aasted Machinery Program

Find the technical specifications for the machine below.

	<b>Master Bottomer 2200</b>	<b>Master Bottomer 1800</b>	<b>Master Bottomer 850</b>	<b>Master Bottomer 2000</b>	<b>Master Bottomer 1050</b>	<b>Master Bottomer 2600</b>	<b>Master Bottomer 1500</b>
<b>Capacity (kg/hour)</b>	Belt width 2200	Belt width	Belt width 850	Belt width 2000	Belt width 1050	Belt width 2600	Belt width 1500
<b>Length (mm)</b>	2500	2500	2500	2500	2500	2500	2500
<b>Width (mm)</b>	2855	24551	1685	2655	1855	2975	2255
<b>Height (mm)</b>	1900	1900	1900	1900	1900	1900	1900
<b>Power usage (KwH)</b>	18	18	18	18	18	18	18
<b>Air usage (m3)</b>	875 l/min	875 l/min	875 l/min	875 l/min	875 l/min	875 l/min	875 l/min
<b>Water usage (m3)</b>	450 l/h	450 l/h	450 l/h	450 l/h	450 l/h	450 l/h	450 l/h
<b>Weight (kg)</b>	2650	2410	1650	2530	2050	2770	2290

	<b>Master Bottomer 1300</b>
<b>Capacity (kg/hour)</b>	Belt width 1300
<b>Length (mm)</b>	2500
<b>Width (mm)</b>	2055
<b>Height (mm)</b>	1900
<b>Power usage (KwH)</b>	18
<b>Air usage (m3)</b>	875 l/min
<b>Water usage (m3)</b>	450 l/h
<b>Weight (kg)</b>	2170

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.