# Alice<sup>™</sup> Z Dynamic Triple







## Alice<sup>™</sup> Z Dynamic Triple

Choose the Alice™ Z Dynamic depositor in triple head configuration and combine up to three different masses into one deposited, extruded or wire-cut product.

Choose le Al se<sup>TM</sup> 1 D mainit de os or ir tripli head co figuration you can couble out to brie different mas on it on elettride of wire cut product. This configuration is used for multi color extrusion, depositing and drop fill depositing (onto conveyor)&ndash create sophisticated and innovative products by combining different masses and fillings. All movements are servo driven and fully programmable. All programming is done from a color touch screen panel and can be adjusted in real time. Choose this configuration if you wish to make fully controlled and complex extruded shapes onto a continuously moving conveyor. This machine is easy to clean. The Alice<sup>TM</sup> hopper also makes it adaptable to quick product changes thanks to its off-line capability.

#### **UPS/EFU**

- Preserves dough structure and texture
- Provides extremely fast change-overs
- Unique "hose-down" cleaning
- Large selection of innovative die tools
- Gently handles dough with inclusions
- Handles aerated masses





### The Aasted Machinery Program

Find the technical specifications for the machine below.

Alice™ Z Dynamic Triple 800         Alice™ Z Dynamic Triple 600         Alice™ Z Dynamic Triple 1200           Length (mm)         1988         2188         1788         2388           Width (mm)         1543         1543         1543           Height (mm)         1878         1878         1878           Power usage (KwH)         50         50         50           Air usage (m3)         75L/min. 6 bar / 4.5         75L/min. 6 bar / 4.5         75L/min. 6 bar / 4.5         50ar / 4.5           Water usage (m3)         20L/h. /         26L/h. /         14L/h. /         32L/h. /					
Width (mm)       1543       1543       1543       1543         Height (mm)       1878       1878       1878       1878         Power usage (KwH)       50       50       50         Air usage (m3)       75L/min. 6 bar / 4.5       75 L/min 6 bar / 4.5       75 L/min 6 bar / 4.5		Dynamic	Dynamic	Dynamic	Dynamic
Height (mm) 1878 1878 1878 1878  Power usage (KwH) 50 50 50  Air usage (m3) 75L/min. 6 75 L/min. 6 75 L/min. 6 bar / 4.5 bar / 4.5 bar / 4.5	Length (mm)	1988	2188	1788	2388
Power usage (KwH) 50 50 50  Air usage (m3) 75L/min. 6 75 L/min 6 75L/min. 6 75 L/min 6 bar / 4.5 bar / 4.5 bar / 4.5	Width (mm)	1543	1543	1543	1543
Air usage (m3) 75L/min. 6 75 L/min 6 75L/min. 6 75 L/min 6 bar / 4.5 bar / 4.5 bar / 4.5	Height (mm)	1878	1878	1878	1878
bar / 4.5 bar / 4.5 bar / 4.5 bar / 4.5	Power usage (KwH)	50	50	50	
Water usage (m3) 20L/h. / 26L/h. / 14L/h. / 32L/h. /	Air usage (m3)				
	Water usage (m3)	20L/h. /	26L/h. /	14L/h. /	32L/h. /

#### We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- Alice™ Z Dynamic Double
- Alice™ Z Dynamic Single