

## Technical Specifications

## Standard and Optional Equipment | ● = standard | □ = optional

Fendt	5275 C	5275 C PL	5275 C PLI	6335 C	6335 C PL
<b>Cutting table</b>					
Table widths FreeFlow from – to (m)	4.80 – 7.60	4.80 – 7.60	4.80 – 7.60	4.80 – 7.60	4.80 – 7.60
Table widths PowerFlow from – to (m)	5.50 – 6.80	5.50 – 6.80	5.50 – 6.20	5.50 – 7.70	5.50 – 6.80
Automatic cutting height control	●	●	●	●	●
Cutting height preselection	●	●	●	●	●
AutoLevel table control	●	●	●	●	●
Automatic reel speed	●	●	●	●	●
Cutting frequency FreeFlow (cuts/min)	1,254	1,254	1,254	1,254	1,254
Cutting frequency PowerFlow (cuts/min)	1,220	1,220	1,220	1,220	1,220
Power Feed Roller	●	●	●	●	●
No. of chains in crop elevator	3	3	3	4	4
<b>Threshing system</b>					
Threshing cylinder width (mm)	1,340	1,340	1,340	1,600	1,600
Threshing cylinder diameter (mm)	600	600	600	600	600
Threshing cylinder speed (rpm)	380 – 1,100	380 – 1,100	380 – 1,100	430 – 1,210	430 – 1,210
Concave angle of wrap	120	120	120	120	120
Concave area (m <sup>2</sup> )	0.83	0.83	0.83	0.99	0.99
Independent front/rear concave adjustment	●	●	●	●	●
Number of concave bars	12	12	12	12	12
Beater diameter (mm)	380	380	380	380	380
<b>Separation</b>					
Multi Crop Separator Plus (MCS Plus)	●	●	●	●	●
MCS Plus width (mm)	1,340	1,340	1,340	1,600	1,600
MCS Plus diameter (mm)	600	600	600	600	600
Active total separation area (m <sup>2</sup> )	1.89	1.89	1.89	2.25	2.25
No. of straw walkers	5	5	5	6	6
Straw walker, no. of steps	4	4	4	4	4
Straw walker length (mm)	4,256	4,256	4,256	4,256	4,256
Straw walker area (m <sup>2</sup> )	5.73	5.73	5.73	6.81	6.81
Total separation area (m <sup>2</sup> )	7.62	7.62	7.62	9.06	9.06
<b>Cleaning</b>					
Grain pan area (m <sup>2</sup> )	2.57	2.57	2.57	3.06	3.06
Total sieve area (m <sup>2</sup> )	4.67	4.67	4.67	5.58	5.58
Total cleaning area (m <sup>2</sup> )	7.24	7.24	7.24	8.64	8.64
Fan type	Radial fan	Radial fan	Radial fan	Radial fan	Radial fan
Fan speed	350 – 1,050	350 – 1,050	350 – 1,050	350 – 1,050	350 – 1,050
Fan speed (with reducer)	270 – 840	270 – 840	270 – 840	270 – 840	270 – 840
Returns to threshing cylinder	●	●	●	●	●
<b>Straw and chaff management</b>					
Straw chopper	●	●	●	●	●
88 serrated knives				●	●
72 serrated knives	●	●	●		
Electrically adjustable deflector plates	□	□	□	□	□
Chaff spreader	□	□	□	□	□
Quick-switch between chopping/swathing	●	●	●	●	●

Fendt	5275 C	5275 C PL	5275 C PLI	6335 C	6335 C PL
<b>Grain tank</b>					
Grain tank capacity (l)	9,000	8,600	8,600	9,000	8,600
Unloading rate (l/sec)	105	105	105	105	105
Grain tank unloading	Top unloading	Top unloading	Top unloading	Top unloading	Top unloading
Unloading auger length (m)	5.0	5.0	5.0	5.0	5.0
Maximum unloading height (m)	4.45	4.45	4.45	4.45	4.45
<b>Engine</b>					
Engine type	AGCO Power	AGCO Power	AGCO Power	AGCO Power	AGCO Power
Type, emissions standard	Tier 4 final	Tier 4 final	Tier 4 final	Tier 4 final	Tier 4 final
Type	6-cylinder	6-cylinder	6-cylinder	6-cylinder	6-cylinder
Cubic capacity (l)	7.4	7.4	7.4	8.4	8.4
Max. power with power boost (kW/hp) (ISO TR14396)	225/306	225/306	225/306	265/360	265/360
Fuel tank capacity (l)	620	620	620	620	620
AdBlue tank capacity (l)	80	80	80	80	80
<b>Ground drive</b>					
Hydrostatic drive	●	●	●	●	●
No. of gears	4	4	4	4	4
Ground speed (km/h)	0 – 25*	0 – 25*	0 – 25*	0 – 25*	0 – 25*
4WD	□	□	□	□	□
ParaLevel slope compensation		●	●		●
<b>Cab</b>					
Skyline cab	●	●	●	●	●
Fendt Variotronic with Varioterminal 10.4"	●	●	●	●	●
Air-suspended driver seat	●	●	●	●	●
Air-conditioning system with heating	●	●	●	●	●
Electrically adjustable heated exterior mirrors	●	●	●	●	●
Additional work lights (stubble light, row finder, rear work lights)	□	□	□	□	□
Multimedia navigator	□	□	□	□	□
Radio	□	□	□	□	□
<b>Variotronic</b>					
Yield and moisture measurement	□	□	□	□	□
VarioGuide	□	□	□	□	□
AgCommand™	●	●	●	●	●
<b>Weights and dimensions</b>					
Length without table (m)	9,040	9,000	9,000	9,040	9,000
Weight base machine, without table (kg)	12,960	14,140	14,780	13,400	14,660
<b>Standard tyres</b>					
Front tyres (standard)	800/65R32	800/65R32	800/65R32	800/65R32	800/65R32
Rear tyres (standard)	460/70R24	540/65R24	540/65R24	460/70R24	540/65R24
<b>Tyres with transport widths (m)</b>					
800/65R32	3,490	3,490	3,490	3,845	3,770
800/65R32	3,645	3,550	3,550	3,900	3,823
710/75R32	3,400	3,400	3,400	3,700	3,683
650/75R32	3,280	3,290	3,315	3,485	3,498

\* depends on country – additional legal constraints may apply.