

Baby Flex Chocolate Compound Sugar Coating



Baby Flex Chocolate Compound Sugar Coating



Baby Flex enrober is supplied in belt width 320 mm, and is well suited for all enrobing works.

The Baby Flex Enrober is carried out in stainless steel and is supplied in bandwidth 320 mm. It is suitable for all enrobing works such as total enrobing, bottoming, partial enrobing and a combination of bottoming and enrobing for all sides of the product. It comes with a wiremesh frame provided with 250 mm infeed wiremesh. An adjustable shaking device for smoothing and removal of surplus coating is also supplied with the machine. The Baby Flex is equipped with a rod detailer for removal of tails at the end of the coated products. The wiremesh table can easily be lifted out of the machine to facilitate the cleaning. Also a moveable heated cabinet containing two extra chocolate hoppers and thermostatically controlled heating element is offered with the Baby Flex. The Baby Flex Enrober is equipped with PLC touch screen and the enrober has working direction left to right.

UPS/EFU

- Uniform coating of products
- Stainless steel
- Great for smaller productions
- Can be disassembled without tools
- High flexibility
- Modular design



The Aasted Machinery Program

Find the technical specifications for the machine below.

Baby Flex 320	
Capacity (kg/hour)	Belt width 320
Length (mm)	910
Width (mm)	600
Height (mm)	1282
Power usage (KwH)	4
Air usage (m3)	0
Water usage (m3)	0
Weight (kg)	150

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

