

MITSUBISHI MITSUBISHI POWER TILLER


MMR66



NEW EASY START ENGINE! "MIRACLE START"

Mitsubishi OHV Engine equipped


Light weight and compact designed GM engine is equipped.
(MMR66 equips GM182LN engine and its max. Output is 6.0 PS.)



6.0PS ENGINE

Easy to operate by mono-change lever

Forward 2 speed, Reverse 1 speed, direction of rotary rotate can be selected by one change lever.



SRT (Standard rotate) & CRT (Counter rotate) rotary

MMR 66 rotary can be selected the direction of rotary tine rotate (standard rotate or counter rotate) by selecting the main change lever position.



Deadman clutch

For the operator safety, clutch will be disengaged when release the hand from handle.

myBOY

MMR66

Differential lock lever

This tiller equips differential gear for making easy turn. And also this tiller equips differential lock (MMR 66 only) and its lever located near by handle for easy operation.

Movable tail wheel

Standard equipment for MMR66



Oil bath type transmission

New aluminum die-cast transmission with oil bath type transmission structure gives high performance of water and dirt proof.

Light weight and new design

Using the light weight engine, aluminum die-cast transmission and plastic cover makes light tiller weight for excellent maneuverability.

SPECIFICATION

Model		MMR66
Dimensions	Overall length (mm)	1,400
	Overall width (mm)	560
	Overall height (mm)	940
Weight (Dry) (kg)		87
Engine	Model	GM182LN
	Type	4Cycle OHV Air-cooled gasoline eng.
	Displacement (L)	0.181
	Rated output (kW [PS] /rpm)	2.6 [3.5] /1500
	Max. output (kW [PS] /rpm)	4.4 [6.0] /1700
	Fuel	Unleaded gasoline
	Fuel tank capacity (L)	2.6
Starting method		Recoil (Miracle Start)

Model		MMR66	
Chassis	Main clutch	V-belt tension type	
	Steering system	Differential gear with lock device	
	Tire size	3.50-7	
	Wheel tread (mm)	390	
	Speed steps	2-forward and 1-reverse	
	Travel speed (m/s)	forward	0.31~1.14
		reverse	0.14
Axle shaft-diameter (mm)	φ19		
Rear tine tiller (Rotary tiller)	Type	Center drive type	
	Tilling width (mm)	500	
	Number of tines	12	
	Rotating speed (rpm)	(standard) 203-(counter) 220	
Others		Movable tail wheel	

Notes: 1. Specifications are subject to change without notice.
2. "Miracle Start" is MHI's trademark.
3. Attachments are options.

MITSUBISHI
AGRICULTURAL MACHINERY CO., LTD.

Gotanda Nomura Shoken Bldg. 6th Floor
1-5-1, Nishigotanda, Shinagawa-ku, Tokyo, 141-0031, JAPAN
PHONE 81-3-5759-8245 FACSIMILE 81-3-5759-8246
<http://www.mam.co.jp>