Pneumatic Linker AT-2






The Linker AT-2 is the indicated tool when a high performance and low investment are required. Its pneumatic operation makes it very robust and reliable in any situation, with very little maintenance.

- Maximum diameter of sausage Ø45.
- Complete stainless steel construction.
- Easy cleaning.
- Great versatility of product to be tie: natural, synthetic, collagen casings... chorizo, sausage, blood sausage, Galician ball (combination of two sizes), etc...
- Finishing tied straight.
- Pneumatic operation.
- Compact design.
- Ties up to 160 portions per minute.

Dimensions

LENGTH (A): HEIGHT(C): *ІППП*ММ WIDTH(B): 750MM. TRAY WIDTH(D): 1460MM WEIGHT: IGDKG.



Technical data

CONSUME: MAXIMUM TYING SPEED PRODUCTION TYING LENGTH MAXIMUM PRODUCT DIAMETER: PRESSURE: PNEUMATIC PRESSURE INDICATOR:

SAFFTY. CONTROLS BASE

GODLIS / MIN IRO PORTIONS / MIN DEPENDING ON SIZE ISMM. TO ISOMM B45 G BAR

GLYCERINE MANDMETER IN CENTRAL PANEL AUTOMATIC STOP WHEN OPENING LID PNFIIMATIC DN/DFF BUTTONS THERMOPLASTIC WITH RUBBER SOLES



Jointed tray for adjustment to different heights of table series.



Autolubricated filter with automatic purae included.



Thread tension adjustment programmable.



The Pneumatic system has an expansion boiler to maintain a constant pressure, minimizing fluctuations in the network.

Options

Kickstart.

Adjustments

- Tying size.
- General speed with regulator.



Abad Maguinaria Industrial S.L. C/Roure Gros 31 - 08181 Sentmenat (Barcelona) ESPAÑA Telf: 93 715 45 13 Fax: 93 715 45 65 laint@laint.net - www.laint.es

