


AUTOMATIC WIRE CUT COOKIE EXTRUDER ST 400 - 600







MADE IN ITALY







Aluminium dosing head easily disassembled for quick change of the moulds (no keys necessary).





Optional









TECHNICAL SPECIFICATIONS

Aluminium frame and covering panels in stainless steel 100 PLC stored programs by color touch screen.

Programming in accordance with IEC norms.

Easy programming in automatic cycle.

Stainless steel dosing rollers at variable speed (inverter).

Tray width 400/600 mm.

Automatic bi-directional electronically controlled trays. advancement at variable speed (inverter). Aluminium dosing head easily disassembled for quick change of the moulds (no keys necessary). Dosing rollers and nozzles rotation at variable speed (inverter)

Wire-cut/extrusion system at variable speed (inverter)

Wire-cut arm wrench in stainless steel/aluminium at 6/9 exits.

Automatic start.

Manual adjustment of conveyor height position.

Anticipated dropping mode.

STANDARD ACCESSORIES

Standard wire-cit mould at 6/9 exits Wire-cut arm wrench Maintenance tool set

Model	Dimensions	Dimensions	Weight	Power	Volt
	[mm] Tray width	[cm] Machine	[Kg]	[kW]	
ST 400 ST 600	400 600	95X137X143H 114X138X143H	278 302	1,48	400x3+T+N 400x3+T+N