


# SF Single L R O



# SF Single L R O


Stationary mounted depositor with dynamic hopper movement. Left/right mounted - can be manufactured to double.

Stationary, right or left mounted and dynamic hopper movement. The SF line represents the flexible depositor with high build quality. The piston axis is servo driven for handling most masses. The rotary axes are optional servo or pneumatically driven. The hopper movement axis is servo driven. The SF is able to easily handle big inclusions. Depositing parts can be delivered in a wide variety to suit the demand, for example, multi-colour, one-shot, inclusions, chips and many more. The SF depositor is available for 500 and up to 1200 lines, working widths ranging from 380 to 1080 mm, however, the depositor can be made to suit any existing lines as well. Operation is very simple via the intuitive touch screen menu. Further the depositor is able to connect to the internet, if any sort of support is needed.

## Picture coming

### UPS/EFU

- Re-configuration of moulding for different products is easy and fast achievable
- Cost-effective
- Servo driven hopper movement
- Ensures high precision depositing
- Easy and simple to operate
- High flexibility



# The Aasted Machinery Program

Find the technical specifications for the machine below.

|                           | soph_flexsf<br>_singlro500 | soph_flexsf<br>_singlro700 | soph_flexsf<br>_singlro100<br>0 | soph_flexsf<br>_singlro120<br>0 |
|---------------------------|----------------------------|----------------------------|---------------------------------|---------------------------------|
| <b>Capacity (kg/hour)</b> | 2300                       | 3900                       | 5900                            | 7500                            |
| <b>Length (mm)</b>        | 1300                       | 1500                       | 2000                            | 2200                            |
| <b>Width (mm)</b>         | 571                        | 571                        | 571                             | 571                             |
| <b>Height (mm)</b>        | 860                        | 860                        | 860                             | 860                             |
| <b>Power usage (KwH)</b>  | 3                          | 3                          | 3                               | 3                               |
| <b>Air usage (m3)</b>     | 12                         | 12                         | 18                              | 18                              |
| <b>Water usage (m3)</b>   | 0,007                      | 0,008                      | 0,01                            | 0,013                           |
| <b>Weight (kg)</b>        | 280                        | 325                        | 390                             | 435                             |

## We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- SF Double L+R O
- SF Double L+R
- SF Double L+R V
- SF Double L+R V O
- SF Single L/R
- SF Single L R V
- SF Single L/R V O
- SF Triple L+R+T
- SF Triple L+R+T O
- SF Triple L+R+T V
- SF Triple L+R+T V O