

# EZ P 600/700

Single-Clip Machine



CLIP LINE<sup>®</sup>  
*Easy*



innovative · reliable · leading

**poly-clip<sup>®</sup>**  
**SYSTEM**

- For bags and netting
- Easy metal detection
- Plastic clips in different colors
- Tight, uniform package every time

## Application

The clipping machines EZ P 600/700 of the Easy Clip Line® are the safe way to package poultry, bakery products, fruits, vegetables and many others in bags or nets. The nonmetal clip allows for an easy metal detection of the finished product. These plastic clips are available in different sizes and colors, and are furnished on spools.

## Advantages

- Patented clip shape with precise guidance of the clip
- Tight, uniform closure every time
- Tight seal
- Clips on spools
- Integral pneumatic cutting knife for short bag tails
- Table and in-built version, right-hand or left-hand
- Fast and smooth operation
- Low air consumption



- Easy to clean
- Low maintenance effort due to only few movable parts
- Low wear and tear
- Coded clips for product identification factory-provided
- Hygiene – stainless steel and industrial plastic
- Processes high-quality clips certified according to FDA and ISO 22000 with compliance of HACCP requirements
- EZ P 600/700 can be combined with the MPL Poultry Loader (bagger)

## Optional equipment

- Horizontal version
- Trolley for horizontal version
- Bracket for mounting on rod at diameters of 35-48 mm
- Pressure reducer with filter
- Labelling system EZ Tag-Feeder (embossing) for tamper-proof product and origin labelling, as well as batch tracing

## Function and operation

The clipping machines EZ P 600/700 are operated pneumatically. By inserting the bag into the gate, the bag is gathered and the plastic clip tightly closes the bag automatically. The optional EZ Tag-Feeder labelling system provides embossed marking on the label, such as best before date and is attached to the

product during clipping.

## Technical Data

Width:	311 mm
Depth:	467 mm
Height:	758 mm
Weight:	15 kg
Compressed air:	5-7 bar/ 0.5-0.7 MPa
Air consumption:	
	5 bar: 2,4 NL/cycle
	7 bar: 2,7 NL/cycle

Suitable clip sizes:  
P 632, P 638, P 744