EZ 8015/9015/P 9015

Single-Clip Machine



innovative · reliable · leading



- Horizontal Single-Clip Machine
- For closure of very heavy and large bags, sacks and nets
- Tamper-proof originality closure
- Made of 100% corrosionresistant stainless steel and industrial plastic

Applications

The horizontal Easy Clip Line® machines EZ 8015/9015/P 9015 safely package substances in granular, powder, liquid or solid form. They are also suitable for dust-free filling by nozzles from above. Possible filling goods in the food sector are, e.g., poultry, fruit or vegetables, and in the non-food sector, e.g. chemical substances such as granules, easily flammable substances, small parts, carpets, blankets, sand, and many other products.

Advantages

- Simple operation
- Quick, tight and reliable closure with uniform packaging
- Safe closing of the separator gate due to two-handed operation
- Hygiene due to stainless steel and industrial plastic with simple cleaning
- Low maintenance effort and wear because there are only few movable parts
- Also suitable for installation in packaging plants
- Processes high quality clips in stick version, certified according to ISO 22000 with compliance of HACCP requirements; plastic clips in addition according to FDA

EZ P 9015

The EZ P 9015 is specially designed for use of plastic clips and is suitable, in particular, for use of metal detectors and for filling of chemical/pharmaceu-



Version EZ P 9015 processes plastic clips.

tical substances, in particular corrosive, toxic and easily flammable substances. Particularly suited for use in locations exposed to the danger of explosions (explosion-proof devices) and clean rooms.

Optional equipment

- Pneumatic knife for shorter product tails:
 - EZ 8015 bottom knife
 - EZ 9015 top or bottom knife
- Easy to move and position due to trolley with fixable wheels to ensure good hold
- Bracket for mounting on rod at diameters of 35-48 mm
- Regulator-lubricator

Function and operation

The clippers EZ 8015/9015/P 9015 operate pneumatically. The filled bags are automatically gathered by insertion into the clip guide slot and closing the separator gate by safe twohanded operation. At the same time, the clipping process is initiated and the product is reliably packaged.

Technical data

EZ 80)/9015	P 9015
Width (mm):	ca.	500
Depth (mm):	ca.	800
Height (mm):	ca.	850-910
Weight (kg):	36	34
Compressed air:		

5-7 bar/0.5-0.7 MPa Air consumption (NL/cycle):

12.3

, 7.9

DOIV-CIIŬ

Suitable clip sizes: EZ 8015: S 844/848/854/860 EZ 9015: S 978/988/998 EZ P 9015: P 911/939/961

Poly-clip System GmbH & Co. KG Niedeckerstraße 1 · 65795 Hattersheim a. M. Germany · Tel. +49 6190 8886-0 contact@polyclip.de · www.polyclip.com