

HOLLYMATIC HIGH VOLUME VACUUM TUMBLERS

FASTER, INNOVATIVE DESIGN GIVES YOU EVEN MORE VALUE!

With our line of Vacuum Tumblers you get more machine for your money and will be able to produce profitable value-added products that your customers will love.

Our tumblers incorporate innovative design, faster production capabilities, and real price/value.

- Available with 300 and 500 pound capacities, these state-of-the-art tumblers draw a vacuum in seconds with bigger and faster vacuum pumps.
- Exclusive touch pad microprocessor controls

store up to 10 programs. You can adjust 3 program segments up to 24 hours and infinitely change speed from 2–15 rotations per minute.

■ A more powerful drive system and stainless steel frame, tank, and cabinet add to the machines' efficiency and durability.

Hollymatic HVTS 300 or 500

Hollymatic's rugged high volume vacuum tumblers create profitable products...easier and faster. Contact Hollymatic or your local Hollymatic dealer today.



HOLLYMATIC VACUUM TUMBLERS GIVE YOU MORE STANDARD FEATURES



HVTS 300 and 500 FEATURES

- A. 4" swivel locking casters make moving tumbler easy
- B. Heavy duty drive train construction
- C. Quick drawing vacuum
- **D.** Two handle lid makes placement easy
- E. Bolt-on extension bar and tank make upgrading easy and affordable
- **F.** Base unit usable for all tumbler upgrades/changes
- **G.** Water separator mounted on side of machine for pump protection and cleaning ease
- H. Photo Electric Safety Beam protects operating area of machine
- I. Touch pad controls
- J. Massaging baffles
- K. Lid Hanger

EXCLUSIVE MICROPROCESSOR FEATURES



- 10 program memory
- 3-24 hour program segments
- Dome switch keypad for friendly programming
- Emergency stop
- Error diagnostic code
- Run/Jog for easy loading and unloading
- Controls variable speed, program lengths and vacuum
- Work/pause capability
- Programs are saved if electrical power is interrupted

SPECIFICATIONS (HVTS 300 or 500)

Power Requirement: 120 Volt, 60 Cycle, 1 Phase, 14A,

220 Volt, 50 Cycle (Optional) **Drive Motor:** 1/2 H.P.

Vacuum Pump: 1 1/4 H.P., 25m3/HR (Reaches operating

vacuum in **seconds!**)

Construction: Stainless Steel Frame, Tank and Cabinet

Capacity: 300 or 500 lb. Batch Sizes **Speed:** Variable From 2–15 RPM

Exclusive Touch Pad Microprocessor Controls

Photo Electric Safety Beam

Mobility: 4-4" Swivel Locking Casters

SIZE DIMENSIONS

HVTS300: 59"L x 40"W x 44"H **HVTS500:** 78"L x 40"W x 44"H

NET. WEIGHT 414 lbs.

414 lbs. 500 lbs.

HOLLYMATIC WARRANTY

Six (6) months from date of purchase. Refer to warranty certificate for terms and conditions Hollymatic Corporation,

600 E. Plainfield Road, Countryside, Illinois 60525 708/579-3700 Fax: 708/579-1057 Web Site: www.hollymatic.com E-mail: hollyinfo@hollymatic.com

