

EP2-0 Belt



EP2-O Belt



The EP2-O Belt is a stationary mounted depositor with a dynamic hopper and offline feature that makes it easily maneuverable for cleaning and switching depositing parts. Built-in lifting table included.

Stationary mounted depositor with dynamic hopper and offline feature that makes it easily maneuverable for cleaning and switching depositing parts. A wide variety of piston diameters can be supplied for production of the smallest pralines up to tablets with big inclusions. The hopper can be divided into multiple compartments for multi-color or one-shot depositing. The belt line depositors have a built-in lifting table. Multiple choices of agitator types are available. The EP2-O Belt Line depositor is available for 700, 750, 1000, 1200 and 1300 mm lines, working widths ranging from 570 to 1170 mm. However the depositor can be made to suit any existing line as well. Operation is very simple via the interactive touch screen menu. Further, the depositor can be connected to the internet, if any sort of support is needed.

UPS/EFU

- Entirely servo-controlled
- Easy to clean
- Fully computerized control
-
- Ultra-flexible and versatile to built into your production line
- Stable and high-quality output



The Aasted Machinery Program

Find the technical specifications for the machine below.

	EP2-O Belt 700	EP2-O Belt 750	EP2-O Belt 1000	EP-2 O belt 1200	EP-2 O belt 1300
Capacity (kg/hour)	3000	3450	4800	5700	6150
Length (mm)	1890	1990	2460	3030	3030
Width (mm)	1700	1700	1700	1700	1700
Height (mm)	1630	1630	1630	1630	1630
Power usage (KwH)	13	13	13	13	13
Air usage (m3)	6	6	6	6	6
Water usage (m3)	0,009	0,01	0,013	0,014	0,015
Weight (kg)	2800	2900	3200	3500	3700

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- EP2 (C-Frame)
- EP2-O (C-Frame)
- EP2-O Chain