

Maschinenfabrik Retus (Erwin Suter AG)

Pickle Injector PM-72

Models

PSM-24-4.5-ZD
PSM-24/48-3.0-ZD

Specifications

- Needlehead with springborne needles
- For injection in products with or without bones
- Stripper bar without pressure to the product
- 1-speed motor (35 strokes/min)
- Conveyor belt removable without tools



Pickle Injector PM-72

		<i>PSM-24-4.5-ZD</i>	<i>PSM-24/48-3.0-ZD</i>
Number of Needles		24 Single Needles	24 Double Needles
Needles spring borne		+	+
Number of Needle Heads		1	1
Diameter of Needles	mm	4.5	3.0
Strokes per Minute	strokes/min		35
Belt Advance per Stroke	mm		30/40
Max. Product Height	mm		180
Channel Width	mm		270
Max. Capacity per Hour	kg	1300 depending on product	
Max. Injection Rate per Pass	%	50	
Pump		Centrifugal Pump	
Drive		Electro-Mechanical	
Needle Head Motor	kW	0.55	
Belt Advance Motor		0.11	
Brine pump	kW	2.2	
Voltage	V/Hz	400/50 *	
Voltage for Control Mode	VDC	24	
Fuses	A/amps	16	
Dimensions	cm	120 × 80 × 200	
Net Weight	kg	200	

* optional