

ET-O (C-Frame)

Picture coming soon

ET-O (C-Frame)

The ET-O (C-Frame) is easily maneuverable for cleaning and re-positioning on the production line. The depositor's dynamic hopper movement is particularly well-suited to deposit filled bars.

With its C-frame, the depositor is easy to move around for cleaning or placing it in another position on the line. With its dynamic hopper movement it is particularly well-suited to deposit, for instance, filling in bars. A variety of piston diameters can be supplied to suit a specific application. Lifting table can be incorporated in the depositor, if needed. The ET-O C-frame depositor is available for Midi, Maxi and Jensen Flex lines, working widths ranging from 350 to 600 mm, however, the depositor can be made to suit any existing lines as well. Operation is very simple via the intuitive touch screen menu. Further, the depositor can be connected to the internet, if any sort of support is needed.

UPS/EFU

- The C-frame design enables frequent production change-overs
- Liquids are handled perfectly
- Easy maintenance and cleaning
-
- Suitable for high-viscosity mass
- The ultimate solution for caramel centre, chocolate chips and other products of high-viscosity mass

Picture coming soon

The Aasted Machinery Program

Find the technical specifications for the machine below.

	ET-O (C-Frame) Midi	ET-O (C-Frame) Maxi
Capacity (kg/hour)	1000	1450
Length (mm)	1675	1675
Width (mm)	1150	1150
Height (mm)	1950	1950
Power usage (KwH)	8	8
Air usage (m3)	2,5	2,5
Water usage (m3)	0,007	0,01
Weight (kg)	1000	1150

We have a broad portfolio of machinery and equipment

Beneath are listed products in the same category.

- ET (C-Frame)
- ET-O Belt
- ET-O Chain